



- AVAILABLE IN 8'-0", 10'-0", & 12'-0" WIDTHS
- BOTH INTERIOR AND EXTERIOR CONCRETE LAYERS ARE PRESTRESSED.
- EITHER INSULATED OR NON-INSULATED
- BOTH LOAD BEARING AND NON-LOAD BEARING
- INSULATION THICKNESS CAN RANGE FROM 1" TO 6".
- PANELS CAN BE ORIENTED EITHER VERTICALLY OR HORIZONTALLY.
- EXTERIOR SCREED FACE APPLIED RAKE OR BROOM FINISHES ARE AVAILABLE.

ARCHITECTURAL FINISHES

- EXPOSED AGGREGATE EXTERIOR FINISH ACCOMPLISHED BY WASHING OR SANDBLASTING PANEL SURFACE.
- AN UNLIMITED VARIETY IF AGGREGATES ARE AVAILABLE TO ACHIEVE A DESIRED COLOR OR TEXTURE.
- WHITE CONCRETE IS AVAILABLE FOR EXTERIOR AND/OR INTERIOR PANEL WYTHES.
- A WIDE VARIETY OF CONCRETE PIGMENTS ARE AVAILABLE TO ACHIEVE A DESIRED COLOR OR EFFECT.
- REVEAL STRIPS AND FALSE JOINTS
- SMOOTH FORM INTERIOR OR EXTERIOR FINISHES
- THIN BRICKS ARE AVAILABLE.

- PANEL CONFIGURATION – FLAT WALL PANEL
DETAIL SCALE: 1/2" = 1'-0"